
Applicant: Masaaki KUREBAYASHI, et al.

Title: Writing Waveform Controlling Method and Optical Disk...

Atty D cket N . 16869P-097100US

Sh et 1 of 9



(650) 326-2400


Applicant: Masaaki KUREBAYASHI, et al.

Titl: Writing Waveform Controlling Method and Optical Disk...

Atty Dock t No. 16869P-097100US

Sheet 2 f 9

FIG.2



(650) 326-2400


Applicant: Masaaki KUREBAYASHI, et al.

Titl: Writing Waveform Controlling Method and Optical Disk...

Atty Dock t No. 16869P-097100US

She t 3 f 9

FIG.3



(650) 326-2400


Applicant: Masaaki KUREBAYASHI, et al.

Titl: Writing Waveform Controlling Method and Optical Disk...

Atty D cket No. 16869P-097100US

She t 4 f 9

FIG.4



Pb RATIO = (Pb3-Pb1)/(Pw-Pb1)

(650) 326-2400


Applicant: Masaaki KUREBAYASHI, et al.

Title: Writing Waveform Controlling Method and Optical Disk...

Atty Docket No. 16869P-097100US

Sh t 5 of 9

FIG.5



 $Pw(c) \times Tmp(c) + Pb3(c) \times (1-Tmp(c)) = Pw(a) \times Tmp(a) + Pb1(a) \times (1-Tmp(a))$

PARAMETERS FOR 3X AFTER CONVERSION (POINT C)

PARAMETERS FOR 3X WRITTEN ON DISK (POINT A)

CORRECTING METHOD


Applicant: Masaaki KUREBAYASHI, et al.

Titl: Writing Waveform Controlling Method and Optical Disk...

Atty D ck t No. 16869P-097100US

She t 6 f 9

FIG.6



(650) 326-2400

Applicant: Masaaki KUREBAYASHI, et al.

Titl: Writing Waveform Controlling Method and Optical Disk...

Atty Dock t No. 16869P-097100US

She t 7 of 9

FIG.7

READ PARAMETERS

OBTAIN PARAMETERS (CONVERTED PARAMETERS) FOR 3X BASED ON PARAMETERS FOR 3X WRITTEN ON DISK (CONDITIONS AT POINT C)

DETERMINE PARAMETERS FOR 2X AND 5X THROUGH TEST WRITE OPERATION

OBTAIN PARAMETERS FOR 3X THROUGH INTERPOLATION AND CORRECTION USING DATA OF 2X AND 5X (CONDITIONS AT POINT B)

DETERMINE MULTI-PULSE PARAMETERS FOR 3X BASED ON PARAMETERS FOR POINTS B AND C USE CONDITIONS AT POINT C AS INITIAL VALUES

AND SHIFT PARAMETERS TO CONDITIONS AT POINT B
WHEN A LARGE NUMBER OF ERRORS HAVE OCCURRED
IN ORDER TO OPTIMIZE PARAMETERS FOR 3X

PERFORM TRIAL WRITE OPERATION AT 4X USING PARAMETERS OBTAINED BY USE OF INTERPOLATION FORMULA AND CHECK ERRORS

ARE ERRORS ACCEPTABLE IN TERMS OF SPECIFICATIONS?

<u>NO</u>

YES

REGISTER STRATEGY OBTAINED ABOVE

(650) 326-2400


Applicant: Masaaki KUREBAYASHI, et al.

Titl: Writing Waveform Controlling Method and Optical Disk...

Atty Docket No. 16869P-097100US

She t 8 f 9

FIG.8




CORRECTING METHOD

Applicant: Masaaki KUREBAYASHI, et al.

Titl: Writing Waveform Controlling Method and Optical Disk...

Atty Dock t No. 16869P-097100US

Sheet 9 f 9



 $\Delta P = (INCLINATION OF IRRADIATION POWER) \times (ADDITIONAL TIME REQUIRED TO REACH SATURATION)$ $\Delta P = (Pw-Pb)/Tr \times (Tr-Tw/2)/2$